

Outdoor PTZ camera for mobile use



this small unit is designed for outdoor observation. The housing body is aluminium and waterproof. The rugged design is proofed up to 10G and works from -40 up to $+60$ degree. You can choose between different SONY camerablocks from 18 x motorzoom up to 36x motorzoom. Also available is a antishock mounting for use on moving objects.



The camera is also available in black

Technical data with SONY FCB 980 camera block

Image Sensor:	1/4" Sony Ex-View CCD, 480VL
Optical Lens & Zoom:	26x (2.2° - 54.2° / 3.5-91mm) 12x Digital
Lens control	Zoom, Focus(auto/man), Iris(auto/man), Mechanical ICR
Camera functions:	White Balance(ATW, AWB, man) / BLC/ Iris(Auto/ Man.)/ Shutter / AE / Day-Night ICR Filter / Image Flip & Mirror
PTZ Characteristics:	360° Pan (0.4°~110° per sec) endless / 120° Tilt (0.4°~60° per sec) with Auto-Flip / Stepless Vario Speed control* / Proportional & constant PT speed.
Automation:	Preset positions(128x) / Preset tours(4x) / Scan tours(4x) / Pattern tracks(4 x 100 sec) / Idle Protection / Scheduled Automation / Start-up assignment.
On-Screen Display:	Date/ Time/ Zoom/ Temperature / Zones/ Name OSD for setup & programming via telemetric.
External I/O	RS485 / BNC Video Output / 4 sensor inputs / 1 Alarm outputs Power Connector
Telemetric:	RS485, 2400 – 19200bps, 16 Multi-Protocol support (Vido B02, Pelco D&P, Panasonic, Samsung..etc)
Shock resistance	10 G
Power Consumption:	DC 10.5 – 15V, <40W , wide power range special for car use
Operation environment:	IP56 weather protection / temperature range -40° ~60°C Humidity up to 95% (environment condition)
Dimension	140mm x180(H)mm, 5Kg.

AVAILABLE SOON, Version with build in AXIS encoder!!

Franz Video Equipment Rev.01/2010